

## Replacing the Monitor on a Big Shot / Mega Shot

### Step # 1

To start the process of removing the monitor you need to remove the marquee from the game. On a big shot you do not need to remove the arms of the game but on a mega shot you should remove the two arms mounted to the sides of the main cabinet.



### Step # 2

Go to the back side of the game and unlock the back upper door of the cabinet. There are two locks for the upper door.



### Step # 3

With the top back door open unplug the 2 pin molex connector for the door mounted fans. These wires should be yellow and black. Once this is unplugged you can remove the spring loaded door hinge and remove the door from the main cabinet. Please place the door aside in a safe place.



## Replacing the Monitor on a Big Shot / Mega Shot

### Step # 4

next unlock the bottom access door. It will open horizontally and pivot down and toward you.



### Step # 5

With the bottom access door open you can unplug the two pin molex connection for the bottom door fans ( circled) and then remove the door by pulling on the spring loaded door hinge pin. Please remove the door and set it aside in a safe place.



### Step # 6

With the door removed reach into the bottom left corner of the main cabinet and unplug the molexes circled in the picture to the right. One connection is a 4 pin square connector with 2 yellow and 2 black wires ( 12 volt dc) and the other circled connections are 2, 2 pin black connections with yellow and black wires ( also 12 volt dc) there are for the lights around the monitor acrylic. At this time also remove the HDMI connection from the monitor and the 110 volt AC power cord from the monitor.



## Replacing the Monitor on a Big Shot / Mega Shot

### Step # 7

For this set it is recommended that you have at least a 2nd person available to steady the monitor cabinet while you remove mounting bolts. Around the outside of the Bump out for the compressor there are 10 M6 machine screws that hold the monitor frame to the base of the cabinet. There are 4 on the top and 3 down each side. they are marked in the pictures to the right. once they are remove the monitor frame will be loose from the cabinet base so hold onto it.



### Step # 8

Once the monitor frame is unbolted from the cabinet base you can use the two handles on each side of the monitor frame to lift the monitor up and off the base. Then you can move it over to a safe place to remove the monitor from the frame. The back of the frame should be facing you when it is leaned against a study wall.



### Step # 9

After the monitor frame is set aside against a study wall you can remove the cross brace from the frame. To do this remove the 6 M4 machine screws from the frame 3 on each side. This will be a tight fit but it will come out and away from the monitor frame.



## Replacing the Monitor on a Big Shot / Mega Shot

### Step # 10

Once the cross brace is removed you can unscrew the monitor from the monitor brackets holding onto the metal frame and remove the bracket to frame screws and the monitor can be removed from the frame.



### Step # 11

With the monitor removed you can transfer over the bracket to the new monitor and reverse step to reinstall the replacement monitor.



### Step # 12

This is for reference so you can see what the main cabinet base will look like with the monitor frame removed.

